


## Aluminum Electrolytic Capacitors

Aluminum Electrolytic Capacitors have a large capacitance per unit volume with a high-capacity area. It is also economically advantaged in the price per unit capacitance compared with other capacitors. It is characterized by the self-restoring property of the derivative (aluminum oxide film) and its tendency not to short. With different forms of **Aluminum Electrolytic Capacitors** such as surface-mounted types and radial-lead types, SUN meets a wide range of user needs by adding such characteristics as low impedance, long life, high reliability and low-profile structure to each specific type.

## Features Aluminum Electrolytic Capacitors



- Wide rated voltage range from 4V to 450V
- Wide capacitance range from 0.47 $\mu$ F to 15'000 $\mu$ F
- Self healing of dielectrics (aluminum oxide film) after damages
- The main failure mode is of wear-out. Short circuit within capacitor is not appreciable
- No voltage dependence of capacitance
- Can withstand applied pulse current and pulse voltage compared to other types of capacitors



AUTHORIZED  
DISTRIBUTOR

# SUNCON Capacitors

## Applications



- Automotive Electronics
- Computer Peripherals
- Network Equipment
- Digital Equipment
- Factory / Enterprise

**ELWET AG**  
[SELATEC](#) | [ELWET](#) | [TELJET](#)  
Electronic and Multimedia Solutions  
Zugerstrasse 22 | CH-6314 Unterägeri  
Fon +41 41 766 00 66

[Contact](#) | [Website](#)

On your disposal for 50 years!

## EP-cap

The **EP-cap** is an aluminum electrolytic capacitor with a hybrid cathode formed by combining an electrolyte and electroconductive polymer with high conductivity. **EP-cap** has very low ESR at high frequency as compared with electrolytic capacitors. The structure of hybrid cathode electrolyte enables **EP-cap** to have the same self healing function as aluminum electrolytic capacitors. EP-cap have hi-reliability product of 125°C (HVP series), 135°C (HVT series) and high voltage up to 125V.

## Features EP-Cap



- Super low ESR (m $\Omega$ )
- Rated voltage up to 125V
- High reliability product of 135°C
- High ripple current (Arms) long life
- Self-healing property of liquid electrolyte
- Excellent low temperature characteristics