



ASTORtex 11346

Double-sided tape made of acrylate-dispersion, with special tissue carrier of high tear strength.

Ideal for use with sealing tapes and die-cut parts, i.e. when mounting is complicated and the parts need to be removable.

Product Properties & Applications

- Suitable as tape for substrates (foam, cork) which provide good adhesion but are removable. Ideal for die-cut parts, which are difficult to mount.
- Suitable for sanitary ware, automotive applications and use in air-conditioning / ventilation equipment.
- soft adhesive film, high adhesive cohesion
- residues after removal of tape are possible
- For use as carpet tape in trade-fair construction
- special tissue for high tear strength
- good resistance to plasticizers and aging
- supplied as rolls from 6 – 1000 mm width and also as die-cuts

Technical Data

Adhesive	Acrylate – dispersion, free from solvents covered side about 40 g/m ² , open side about 150 g/m ²
Carrier	special closed-meshed tissue
Liner	siliconized, white paper
Thickness of tape	ca. 0.21 mm
Adhesive strength DIN EN 1939	ca. 10 N/ 25 mm on open and covered side
Tensile Strength DIN 53857	200 N/50 mm
Resistance to shear – dynamic	20 N/cm ²
Temperature resistance	-40°C to +90°C
Resistance to condensated water	good
Ageing resistance	very good
Resistance to plasticizers	very good

All data are single values and are not to be considered as specifications We recommend to perform own tests to ensure suitability